

TATA MOTORS



SUMO

UNLEASH POWER INTO YOUR LIVES WITH THE
UNSTOPPABLE SUMO. ITS ROBUST 483 DL TC ENGINE
GIVES YOU A COMMAND OVER EVERY TERRAIN WHILE
YOU SET OUT TO MAKE NEW ROADS WHEREVER YOU GO.



PEDIGREE

The Tata Sumo has an imposing poise, broad & stable stance which is enhanced by stylish body graphics. The headlight design works in tandem with a prominent tail-lamp cluster, powerful front & rear fog lamps, to light up the path. Choice of 15"/ 16" wheels and a high ground clearance of upto 180 mm, make it a perfect off-roader for both large families and small businesses over good roads, bad roads and even no roads.



COMFORT AND CONVENIENCE

Sumo's performance is only amplified by its driver -friendly features such as power steering, tilt-able steering wheel, remote tailgate latch and more. There's always room for more when you drive a Sumo where you have an option to seat 9 passengers along with the driver or a choice of folding the seats to accommodate luggage.



UNDER THE HOOD

The Sumo goes a step ahead with a powerful & reliable 483 DL TC engine which is designed to ensure maximum fuel efficiency in the most economical way.



UTILITY

The Sumo comes with the promise of superior space and comfort for all kinds of roads. It is an ideal choice for those running a small business on rough terrain and people with large families. For over two decades, Sumo has been the best-selling MUV across the nations with hilly terrains, favoured for its low cost of ownership.



SPECIFICATIONS

ENGINE, DRIVETRAIN & CHASSIS		
Model	Tata 483 DLTC 50 (4x2)	Tata 483 DL TCIC (4x4)
Type	Watercooled, Indirect Injection. Watercooled Indirect Injection with Turbocharged, Intercooled Diesel with Crankcase Breather and Relief Valve	
Bore/Stroke (mm)	83 x 90	
Capacity (cc)	1948	
Compression Ratio	21 : 1	
Max. Engine Output (PS @ rpm)	90/4300	87/4300
Max. Torque (Nm @ rpm)	186 @ 2500	190 @ 2000-3000
Max. Speed (kmph)	115	115
Gear Box Type	Synchromesh on All Gears	
No. of Gears	5 Forward and 1 Reverse Gear	
Brakes	Disc Brakes at Front & Rear	
Tyres	215/75 R15 LT 106 S Tubeless	205/80 R16 Radial Tubeless Alloy Wheels
Wheel Rims	5.5 J x 15"	6.5 J x 16"
Suspension-Front	Double Wishbone with Coil Springs	Double Wishbone with Torsion Bar Springs
Suspension-Rear	Semi - Elliptical Leaf Springs	
Shock Absorber	Hydraulic Double Acting Telescopic Type at Front & Rear	
DIMENSIONS & WEIGHTS		
Wheelbase (mm)	2400	2435
Overall Length (mm)	4285	4450
Overall Width (mm)	1728	1780
Overall Height (mm)	1976/1906 (Unladen/Laden)	1975/1905 (Unladen/Laden)
Ground Clearance (mm)	160	180
Max. G.V.W. (kg)	2540	2710
Max. Vehicle Kerb Weight (kg)	1820	1900
Min. Turning Circle Radius (m)	5	5.9
Fuel Tank Capacity (ltr)	65	
Seating Capacity	9 Persons and Driver	
Net Luggage Space (ltr)	450	

DEALER STAMP:

FEATURES

STYLE

Body Coloured Rear View Mirrors & Door Handles | Body Side Claddings | Full Fabric Upholstery | Soft Feel Four Spoke Steering Wheel

CONVENIENCE

Power Steering | Power Windows | Tilttable Steering Wheel | Vanity Mirror on Sun Visor for Co-Driver | Remote Release for Fuel Lid Latch and Tailgate Latch | Cigarette Lighter and Ash Tray

SAFETY & SECURITY

Remote Central Locking | Anti-Theft Device-Immobilizer, Ignition-Cum-Steering Lock | Child Safety Lock on Rear Doors | Front Seat Belt with Retractor - ELR Type | Rear Seat Belts-Sides-ELR Type | Anti - Submarine Front Seats with Head Restraints | Height Adjustable Front Headrest | Front and Rear Fog Lamps

COMFORT

Air-conditioning | Roof Air-conditioner for Rear Compartments | Independent Front and Leaf Springs Rear Suspension for Enhanced Ride Comfort