

BOLERO MAXITRUCK PLUS VX

- Large cargo deck
- Wider radial tyres with higher load carrying capability
- Improved LSPV braking system for better safety
- Large 25.4 wheel brake cylinder for efficient braking
- Stronger rear leaf spring suspension for carrying heavier cargo



Mahindra
Rise.

UNMATCHED PERFORMANCE

- Powerful engine with 63 BHP (46.3 kW) power and best-in-class 195 Nm torque
- Rigid leaf-spring front suspension that's designed for all kinds of terrain
- Large 15 inch (38.1 cm) tyres for better grip and higher ground clearance
- Long wheelbase of 3150mm for better stability
- Strong body and chassis that reduces wear and tear

UNMATCHED DRIVABILITY

- Lower turning radius of 5.5m for maneuvering through small lanes and by lanes
- Power steering option for easy turning

UNMATCHED ASSURANCE



- Front-nose design for enhanced safety
- 1 year 50,000 kms warranty (highest-in-class)
- Solid build and rugged design
- Vehicle immobiliser for safety against theft
- Wide service network with easy availability of spares

UNMATCHED STYLE AND CONVENIENCE

- Attractive bold front grille
- Eye-catching wrap around headlamps
- Trendy dual-tone instrument panel
- Comfortable fabric seats with matching door trims
- Mobile holder and charging point

UNMATCHED EARNINGS

- Large cargo deck of 40.6 sq.ft (3.7 sq.m) to carry more load per trip
- 1670kg payload for carrying heavy loads effortlessly
- Best-in-class fuel economy
- Low on maintenance



LOAD SENSING PROPORTIONING VALVE (LSPV)

It adjusts braking pressure as per the load in the pickup. When the vehicle is heavily loaded, LSPV regulates brake pressure to the rear brakes to prevent locking of tyres. LSPV improves braking performance and enhances safety on any road and any incline, no matter what the cargo load is.

TECHNICAL SPECIFICATIONS

ENGINE	
Model	m2DiCR 4 Cyl 2.5L TA / TB
Type	DI, Turbo charged
No. of cylinders	4
Displacement	2523cc
Maximum Engine Output	63 BHP (46.3 kW) @ 3200 rpm
Maximum Torque	195 Nm @ 1400-2200 rpm
CLUTCH	
Type	Single plate dry clutch

TRANSMISSION	
Model	NGT 520
No. of gears	5 forward, 1 reverse, All synchromeshed
STEERING	
Type	Manual (Standard), Power steering (Optional)
WHEEL & TYRES	
Rim diameter	15 inch (38.1 cm)
Tyre size	215/75 R 15

FUEL TANK	45 litres
PAYLOAD (kg)	1670
MAXIMUM GVW (kg)	3140
VEHICLE DIMENSION	
Overall (mm)	4925 x 1700 x 1835
Wheelbase (mm)	3150
Cargo-body (mm)	2500 x 1620 x 458
SUSPENSION	
Front	Rigid with semi-elliptical

Rear	leaf springs, with anti-roll bar at front
BRAKES	Rigid with semi-elliptical leaf springs
SEATING CAPACITY	Front - Disc; Rear - Drum
AVAILABLE IN COLOURS:	1+1
	Diamond White
	Bold Beige

**BOLERO
MAXITRUCK
PLUS VX**

Mahindra & Mahindra Ltd. International Operations, Auto & Farm Equipment Sectors, 2nd Floor, Mahindra Towers, Worli, Mumbai 400 018, Tel +91-22-24905773.

All features and colours mentioned are not available on all models • Accessories shown are not part of standard equipment • Performance figures may differ in conditions other than test conditions • Vehicle body colour may differ from the printed photographs • In view of our policy of continuously improving our products, we reserve the right to alter specifications or designs without prior notice and without liability • Please check model details with your nearest dealer.

Dealer Stamp

